

Technical Data Sheet

20-016 2K Polyester Soft Putty

Characteristics:

Multi-purpose, soft putty with filling properties. It contains fine-grained and lightweight fillers. Characterized by creamy consistency, this putty is very easy to apply and to model, even on vertical surfaces. It may be applied in both thin and thick layers. It creates an elastic and very smooth, pore-free coating. This putty is easy to sand and doesn't clog the sandpaper. It adheres to steel, aluminium and polyester surfaces.

Application:

The surface must be clean, dry, degreased and matted with abrasives. Thoroughly mix putty by weight with 2-3% of BPO hardener. Apply within 4 - 6 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time.

Note:

Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C. Do not apply on wash primers and one component acrylic products.

Technical data:

Density: 1,65 g/cm³


Color: beige




2004/42/IB(b)(250)<250




Cleaning



Putty 100g
BPO hardener 2g



Pot life:
4-6 min at 20°C



Drying time:
16 - 26 min at 20°C




Hand sanding / dry:
P120 - P240



Machine sanding / dry:
P120 - P240



Store in cool place



Shelf life:
12 Month

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products.

Copyright: Q-Company 2017, all rights reserved.

Q-Company Int. GmbH / Beckershof 3 / D-24558 Henstedt-Ulzburg / Germany

Version: 02.01.2017