



Product name	:	MoTip Plastic Primer	
Article number	:	04063	
Supplier / Producer	:	MOTIP DUPLI B.V. Wolframweg 2 NL-8471 XC WOLVEGA	
		Telephone number	+31 561 – 69 44 00
		Telefax number	+31 561 – 69 44 31

---

### Product description

High quality, fast drying plastic primer to treat surfaces, treated and untreated, of several types of plastic.

### Product characteristics

Fast drying  
Excellent adhesion  
Re-sprayable with all lacquer systems  
Not suitable for treatment of PE.

### Physical and Chemical Characteristics

Contents	:	400 ml
Base	:	Polyolefine resin
Colour	:	Transparent
VOC-content	:	Approximately 99% w/w
Solid content	:	Approximately 1% w/w
Coverage	:	2 to 3 m <sup>2</sup>
Re-sprayable	:	After 10 to 15 minutes

### Usage

**Before use, carefully read the directions on the packaging and act accordingly.**

#### Pre Treatment

The surface should be clean, dry and free of grease. When desired, slightly sand the surface, grain 600.

#### Treatment

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the plastic primer in maximum two (2) thin layers. After drying, without sanding, re-sprayable with all lacquer systems.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

**The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.**