




MC885 – MACROFAN UHS FADE-OUT BLENDER



Ready for use

DESCRIPTION

Fade-out blender for UHS topcoats.

USE

It blends and makes uniform the fade-out in refinishing with solvent-based topcoats, topcoat MACROFAN UHS MAC4 and MACROFAN UHS CLEARCOATS. It also makes polishing easier.

CHARACTERISTICS

- It makes touch-up easy
- It improves and makes polishing easier
- Good solvent power
- Balanced solvents release

APPLICATION

After the touch-up or the fade-out, spray 1-2 light coats of the product on the fade-out area as quick as possible, 1-2 min., allow it to dry and then, if necessary, polish with 00917 POLISH PASTE WATER-BORNE (see polishing process technical data sheet n° CL023).

Moreover, it is possible to dilute the topcoat (MACROFAN UHS) with a part mix of MC885 (mixing ratio MACROFAN UHS / MC885 1:1), by widening the fade-out edge and then finishing the application just with MC885.

After drying, if necessary, it is possible to polish with 00917 POLISH PASTE WATER-BORNE.

**TECHNICAL DATA SHEET N° 0641-GB
UPDATED 10/2008**

All information contained in this data sheet is the result of carefully controlled tests and is correct to the best of Lechler's knowledge at the time of issue. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated and the manner of use is the sole responsibility of the user. FOR PROFESSIONAL USE ONLY.